

SECTION 1: IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Deluxe Coatings EZY TEX - ROLLON TEXTURE PAINT - SAND FREE (NO SAND)

Product Type: Water-borne Pure Acrylic Emulsion

Recommended Uses: Premium, 100% acrylic waterborne architectural texture coating for interior feature walls and exterior facade applications.

Restrictions on Use: Use only as directed on technical documentation.

Manufacturer: DELUXE COATINGS

Address: Unit 5/65 Holder Way, Malaga, WA 6090

Phone / Mobile: 9259 4113 / 0400 736 466

Email / Web: deluxecoatingsmalaga@gmail.com | deluxecoatings.au

Emergency Phone: **Contact local poison information services or seek immediate medical attention.**

SECTION 2: HAZARDS IDENTIFICATION

SIGNAL WORD: WARNING

GHS CLASSIFICATION

- **Acute Toxicity (Oral):** Category 4
- **Skin Sensitisation:** Category 1 (Contains biocide/fungicide preservatives)
- **Serious Eye Irritation:** Category 2A
- **Hazardous to Aquatic Environment (Chronic):** Category 3

HAZARD STATEMENTS

- Harmful if swallowed.
- May cause an allergic skin reaction.
- Causes serious eye irritation.
- Harmful to aquatic life with long-lasting effects.

PRECAUTIONARY STATEMENTS - GENERAL & PREVENTION

- **General:** Keep out of reach of children. Read label before use.
- **Prevention:** Ensure good ventilation during application and drying. Wear approved eye protection (AS1337). Wash thoroughly after handling.

PRECAUTIONARY STATEMENTS - RESPONSE & DISPOSAL

- **IF SWALLOWED:** Do NOT induce vomiting. Call a POISON CENTER or doctor/physician.
- **IF ON SKIN:** Wash with plenty of soap and water.
- **IF IN EYES:** Rinse cautiously with water for several minutes; seek medical advice.
- **Disposal:** Dispose of contents/container in accordance with local environmental regulations.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Entity	CAS Number	Weight %
100% Acrylic Co-polymer Emulsion	Proprietary	50% – 60%
Lightfast Pigments & Fillers	Proprietary	20% – 30%
Cellulosic Rheology Modifiers	Proprietary	1% – 5%
Ammonia (pH Adjuster)	1336-21-6	< 1%
Dual Biocide / Fungicide System	Mixture	< 1%
Water / Non-hazardous Ingredients	7732-18-5	Balance to 100%

SECTION 4: FIRST-AID MEASURES

Inhalation:	Move affected person to fresh air. Ensure adequate ventilation. If symptoms persist, seek medical attention.
Skin Contact:	If accidental skin contact occurs, wash area immediately with plenty of soap and water or a recognized skin cleaner.
Eye Contact:	Immediately rinse eyes cautiously with plenty of clean running water. Remove contact lenses if present and easy to do. Continue rinsing and seek medical advice.
Ingestion:	Harmful if swallowed. Do NOT induce vomiting. Seek immediate medical attention.
Immediate Care:	Treat symptomatically based on exposure route.

SECTION 5: FIRE-FIGHTING MEASURES

Flammability:	Non-flammable water-based liquid.
Extinguishing:	Water spray, foam, dry chemical, or carbon dioxide (CO ₂) appropriate for surrounding fire.
Hazards:	Thermal decomposition may release carbon oxides and trace organic vapors.
Protective:	Wear self-contained breathing apparatus (SCBA) and full protective bunker gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Ensure adequate ventilation. Avoid contact with eyes and prolonged contact with skin. Wear appropriate personal protective equipment (eye protection AS1337).

Environmental Precautions: Prevent product from entering drains, waterways, or soil.

Containment & Cleanup: Contain spillage with non-combustible absorbent materials (sand, earth, vermiculite). Wipe or scoop up spillage. Brush remaining material onto newspaper, allow to dry completely, and dispose of via solid waste collections. Clean spill area immediately with warm, soapy water.

SECTION 7: HANDLING AND STORAGE

Safe Handling: Keep out of reach of children. Ensure good ventilation during application and drying. Avoid contact with eyes and skin. Wear AS1337 approved eye protection. Do not eat, drink, or smoke when using this product.

Storage Conditions: Store in original, unopened containers in a dry, well-ventilated area. Protect from freezing and direct sunlight.

Storage Temperature: Ambient storage temperatures between 5°C and 35°C.

Incompatibilities: Strong oxidizing agents, strong acids.

Shelf Life: 24 months from manufacturing date in unopened containers under recommended conditions.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters (VOC): VOC content < 50 g/L (EPA Method 24 / EU limits compliant).

Engineering Controls: Maintain adequate general dilution or local exhaust ventilation during mixing, application, and drying to ensure low odor and low VOC levels.

Personal Protective Equipment (PPE):

- **Eye/Face Protection:** Protective goggles/glasses approved to AS1337 must be worn while handling.
- **Skin Protection:** Wear protective gloves (nitrile or rubber) and standard protective clothing.
- **Respiratory Protection:** If spraying in confined spaces without adequate ventilation, wear an approved organic vapor/particulate respirator meeting AS/NZS 1716 standards.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical Property	Value / Specification	Reference Standard
Appearance / State	Viscous liquid (Matt, Smooth Textured finish)	Visual Inspection
Color	White & tintable to pastel spectrum	Visual Inspection
Odor	Mild acrylic / slight ammonia odor	Internal
Resin / Binder Type	100% Premium Acrylic Co-polymer Emulsion	Technical Spec
pH Value	8.0 – 9.0 (adjusted using ammonia)	pH Meter
Specific Gravity / Density	1.40 - 1.55 g/cm ³	ISO 2811
Viscosity	110 – 125 KU at 25°C	ASTM D562
Solids Content	Volume: 50% – 60% Weight: 60% – 70%	Internal / ASTM D2697
Flash Point	Non-flammable / Not Applicable (Waterborne)	Waterborne System
VOC Content	< 50 g/L	EPA Method 24 / EU Limits
Solubility	Miscible in water (un-cured film)	Internal

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Stable under normal conditions of use and storage.

Chemical Stability: Stable under recommended storage temperatures (5°C to 35°C).

Hazardous Reactions: No dangerous reactions known under normal handling.

Conditions to Avoid: Extreme heat (>40°C), direct sunlight, and freezing conditions (<5°C).

Incompatible Materials: Avoid strong oxidizing agents, strong acids, or unapproved chemical additives.

Hazardous Decomposition: Thermal decomposition under fire conditions may produce carbon monoxide, carbon dioxide, and minor organic vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity: Low acute oral and dermal toxicity.

Skin Contact: Prolonged or repeated contact may cause mild irritation or skin dry-out.

Sensitization: Contains active anti-fungal/anti-microbial additives which may trigger sensitivity in hyper-susceptible individuals.

Eye Contact: Direct splash may cause eye irritation and temporary discomfort.

Ingestion: Swallowing may cause gastrointestinal discomfort, nausea, and vomiting.

Carcinogenicity / Mutagenicity: Components are not classified as carcinogenic or mutagenic under standard GHS limits.

SECTION 12: ECOLOGICAL INFORMATION

Eco-Toxicity: Avoid contaminating drains and waterways.

Rainwater System Precautions: Disconnect all downpipes feeding rainwater collection tanks or storm drains prior to cleaning and coating. Leave downpipes disconnected for at least 14 days or until after the first two heavy rainfalls to flush away residual surface surfactants.

Environmental Disposal: Dry unwanted paint on newspaper prior to domestic disposal.

Bioaccumulative Potential: Low potential.

Persistence and Degradability: Acrylic binder matrix persists; organic additives biodegrade over time.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Treatment / Product Disposal: Do NOT pour leftover paint down drains or sewers. Unwanted liquid paint should be brushed out on newspaper, allowed to dry completely, and disposed of via domestic solid waste collections.

Container Disposal: Empty paint containers should be left open in a well-ventilated area to dry out completely. When dry, recycle containers via appropriate municipal recycling programs.

SECTION 14: TRANSPORT INFORMATION

UN Number:	None (Non-regulated)
Shipping Name:	Paint (Water-borne, non-flammable)
Hazard Class:	Not classified as Dangerous Goods
Packing Group:	Not applicable
Environmental:	Non-hazardous for transport
Precautions:	Transport in cool, upright containers. Prevent freezing and direct solar heating.

SECTION 15: REGULATORY INFORMATION

Standards Compliance:

- **Eye Protection Standard:** AS1337 compliant.
- **VOC Regulations:** Complies with EPA Method 24 / EU limits (< 50 g/L).
- **Solids / Drying Standards:** ASTM D2697 (Solids), ISO 2811 (Density), ASTM D562 (Viscosity), ASTM D1640 (Drying).
- **Poisons Schedule (SUSMP):** Not scheduled / Non-hazardous waterborne system.

SECTION 16 & 17: OTHER INFORMATION, LEGAL DISCLAIMER & WARRANTY

SDS Version: 1.0 | **Document Issue Date:** July 2026 |

Packaging Sizes: 10L & 15L

Manufacturer Note: Always perform a test patch in an inconspicuous area if you are unsure of the substrate's condition. For technical support, contact the Malaga office.

Product Warranty: Deluxe Coatings warrants that this product, when applied in strict accordance with the instructions on the packaging and this Technical Data Sheet (TDS), will meet its published performance specifications. This warranty extends for up to 10 years for exterior applications and 12 years for interior applications from the date of purchase.

Limitations & Coverage: This warranty covers product replacement or refund of the purchase price only. It excludes failure resulting from inadequate surface preparation, structural movement, hydrostatic pressure, rising damp, improper thinning, or mechanical damage. To the maximum extent permitted by law, Deluxe Coatings is not liable for labor, scaffolding, or consequential damages.

Disclaimer & Notice: Information and recommendations in this document are provided in good faith based on laboratory testing and field experience. Because substrate conditions, application methods, and environmental factors are beyond our control, users must determine the suitability of the product for their intended use. Deluxe Coatings reserves the right to update product formulations and technical data without prior notice. Always ensure you are referencing the most current TDS available on the official Deluxe Coatings portal.