

DELUXE COATINGS

New Gloss Acrylic Enamel Trim Paint

SAFETY DATA SHEET

Issue Date: July 2026

SDS Version: 1.0 (GHS Compliant)

Product Code: 100% Premium Acrylic

SECTION 1: PRODUCT & COMPANY IDENTIFICATION

Product Identifier: Deluxe Coatings New Gloss Acrylic Enamel Trim Paint

Other Names: Deluxe Water-Based Acrylic Enamel Trim Paint

Product Type: 100% Premium Acrylic Water-Based Gloss architectural coating

Recommended Use: High-wear trim surfaces including architectural trim, skirting boards, architraves, doors, frames, window sashes, timber shutters, handrails, cabinet surfaces, and wet area trim. Suitable for primed wood, cured masonry, aluminum, and previously painted enamel.

Restrictions: Use only as directed on technical documentation.

MANUFACTURER / SUPPLIER DETAILS

Company: DELUXE COATINGS

Address: Unit 5/65 Holder Way, Malaga, WA 6090

Phone: 9259 4113

Mobile: 0400 736 466

Email: deluxecoatingsmalaga@gmail.com

Website: deluxecoatings.au

Emergency: Contact local poison information services or seek immediate medical attention.

SECTION 2: HAZARD(S) IDENTIFICATION

SIGNAL WORD: WARNING

GHS Classification: Acute Tox. 4 (Oral) | Skin Irrit. 3 | Eye Irrit. 2B

HAZARD STATEMENTS:

- H302: Harmful if swallowed.
- H316: May cause mild skin irritation.
- H320: Causes eye irritation.

*Contains minor active anti-fungal/anti-microbial additives and trace volatile bases (ammonia).

PRECAUTIONARY STATEMENTS:

- General: Keep out of reach of children. Read label before use.
- Prevention: Ensure good ventilation. Wear approved eye protection (AS1337). Wash thoroughly after handling.
- Response: IF SWALLOWED: Do NOT induce vomiting. Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water; seek medical advice.
- Disposal: Dispose of contents/container in accordance with local environmental regulations.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Identity / Component	CAS Number	Proportion (w/w)
100% Premium Acrylic Emulsion Binder	Proprietary	30 – 50%
Lightfast Pigments & UV Stabilizers	Commercial blend	10 – 30%
Active Anti-Fungal / Anti-Microbial Additives	Proprietary	< 2%
Ammonia (pH Adjuster)	1336-21-6	< 0.5%
Water & Non-Hazardous Additives	7732-18-5	Balance to 100%

SECTION 4: FIRST-AID MEASURES

Inhalation: Move affected person to fresh air. Ensure adequate ventilation. If symptoms persist, seek medical attention.

Skin Contact: Wash area immediately with plenty of soap and water or a recognized skin cleaner.

SECTION 5: FIRE-FIGHTING MEASURES

Flammability: NON-FLAMMABLE Water-based liquid.

Extinguishing Media: Water spray, foam, dry chemical, or carbon dioxide (CO2) appropriate for surrounding fire.

Specific Hazards:

Eye Contact: Immediately rinse cautiously with plenty of clean running water. Remove contact lenses if present. Continue rinsing and seek medical advice.

Ingestion: **Harmful if swallowed. Do NOT induce vomiting.** Seek immediate medical attention.

Medical Advice: Treat symptomatically based on exposure route.

Protective Equipment: Thermal decomposition may release carbon oxides and trace organic vapors. Wear self-contained breathing apparatus (SCBA) and full protective bunker gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- **Personal Precautions:** Ensure adequate ventilation. Avoid contact with eyes and prolonged skin contact. Wear AS1337 eye protection.
- **Environmental Precautions:** Prevent product from entering drains, waterways, or soil.
- **Containment & Cleanup:** Contain spillage with non-combustible absorbent materials (sand, earth, vermiculite). Wipe/scoop up spillage. Brush remaining material onto newspaper, allow to dry completely, and dispose via solid waste. Clean spill area immediately with warm, soapy water.

SECTION 7: HANDLING AND STORAGE

- **Safe Handling:** Keep out of reach of children. Ensure good ventilation. Avoid contact with eyes/skin. Wear AS1337 eye protection. Do not eat, drink, or smoke when using.
- **Storage Conditions:** Store in original, unopened containers in a dry, well-ventilated area. Protect from freezing and direct sunlight.
- **Storage Temp:** 5°C to 35°C.
- **Incompatibilities:** Strong oxidizing agents, strong acids.
- **Shelf Life:** 24 months from manufacturing date in unopened containers.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters & Engineering:

VOC Content: < 50 g/L (EPA Method 24 / EU limits compliant).

Engineering Controls: Maintain adequate general dilution or local exhaust ventilation during mixing, application, and drying to ensure low odor and low VOC levels.

Personal Protective Equipment (PPE):

- Eye/Face:** Protective goggles/glasses approved to **AS1337** must be worn while handling.
- Skin Protection:** Wear protective gloves (nitrile or rubber) and standard protective clothing.
- Respiratory:** If spraying in confined spaces without adequate ventilation, wear an approved organic vapor/particulate respirator meeting **AS/NZS 1716** standards.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Property	Value / Description
Appearance	Liquid - White & tintable pastel bases
Finish	High Gloss (80-85% @ 60°)
Odor	Low Odor
Binder Type	100% Premium Acrylic copolymer
Solids Content	Volume: 40% ± 2% Weight: 50% ± 2%
Specific Gravity (SG)	Approx. 1.15 – 1.25 g/cm³
Viscosity at 23°C	95 - 100 KU (Krebs Units) at 25°C

Property	Value / Description
pH Value	8.0 – 9.0 (Adjusted using Ammonia)
Flash Point	Non-flammable
VOC Content	< 50 g/L
Spreading Rate	10 – 12 m²/L per coat at 60 µm DFT
Freezing Point	Not determined (protect from < 5°C)
Solubility in Water	Dispersible prior to curing; cured film is water repellent
Drying Times (25°C & 50% RH)	Touch Dry: 30–60 min Recoat: Min 2–4 hrs Full Cure: 7–14 days

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Stable under normal conditions of use and storage.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity: Low acute oral and dermal toxicity.

Skin Contact:

Stability:	Stable under recommended storage temperatures (5°C to 35°C).
Hazardous Reactions:	No dangerous reactions known under normal handling.
Conditions to Avoid:	Extreme heat (>40°C), direct sunlight, and freezing (<5°C).
Incompatibilities:	Strong oxidizing agents, strong acids, unapproved chemical additives.
Decomposition:	Thermal decomposition under fire may produce CO, CO ₂ , and minor organic vapors.

Sensitization:	Prolonged or repeated contact may cause mild irritation or skin dry-out.
Eye Contact:	Contains active anti-fungal/anti-microbial additives which may trigger sensitivity in hyper-susceptible individuals.
Ingestion:	Swallowing may cause gastrointestinal discomfort, nausea, and vomiting.
Carcinogenicity:	Components not classified as carcinogenic or mutagenic under GHS limits.

SECTION 12: ECOLOGICAL INFORMATION

- **Eco-Toxicity:** Avoid contaminating drains and waterways.
- **Rainwater System Precautions:** Disconnect all downpipes feeding rainwater collection tanks or storm drains prior to cleaning and coating. Leave downpipes disconnected for at least 14 days or until after the first two heavy rainfalls to flush away residual surface surfactants.
- **Environmental Disposal:** Dry unwanted paint on newspaper prior to domestic disposal.
- **Bioaccumulative Potential:** Low potential.
- **Persistence / Degradability:** Acrylic binder matrix persists; organic additives biodegrade over time.

SECTION 13: DISPOSAL CONSIDERATIONS

- **Waste Treatment / Product Disposal:** Do NOT pour leftover paint down drains or sewers. Unwanted liquid paint should be brushed out on newspaper, allowed to dry completely, and disposed of via domestic solid waste collections.
- **Container Disposal:** Empty paint containers should be left open in a well-ventilated area to dry out completely. When dry, recycle containers via appropriate municipal recycling programs.

SECTION 14: TRANSPORT INFORMATION

UN Number:	None (Non-regulated)
Shipping Name:	Paint (Water-borne, non-flammable)
Transport Class:	Not classified as Dangerous Goods for transport.
Packing Group:	Not applicable
Hazards:	Non-hazardous for transport.
Precautions:	Transport in cool, upright containers. Prevent freezing and exposure to direct solar heating.

SECTION 15: REGULATORY INFORMATION

- **Eye Protection Standard:** AS1337 compliant.
- **VOC Regulations:** Complies with EPA Method 24 / EU limits (< 50 g/L).
- **Standards Compliance:** ASTM D2697 (Solids), ISO 2811 (Density), ASTM D562 (Viscosity), ASTM D1640 (Drying).
- **Poisons Schedule (SUSMP):** Not scheduled / Non-hazardous waterborne system.

SECTION 16: OTHER INFORMATION

SDS Version: 1.0

Document Issue Date: July 2026

Packaging Sizes Covered: 1L, 2L, 4L, 10L & 15L

SECTION 17: LEGAL DISCLAIMER & PRODUCT WARRANTY

Product Warranty: Deluxe Coatings warrants that this product, when applied in strict accordance with instructions on the packaging and Technical Data Sheet (TDS), will meet published performance specifications. This warranty extends up to 10 years for exterior applications and 12 years for interior applications from purchase date.

Limitations & Coverage: Covers product replacement or refund of purchase price only. Excludes failure resulting from inadequate surface preparation, structural movement, hydrostatic pressure, rising damp, improper thinning, or mechanical damage. Not liable for labor, scaffolding, or consequential damages.

Disclaimer & Notice: Information provided in good faith based on laboratory testing and field experience. Substrate conditions and application methods are beyond our control. Users must determine suitability for intended use.

MANUFACTURER'S NOTE: Always perform a test patch in an inconspicuous area. For technical support, contact the Malaga office. Formulations subject to update without prior notice.