

DELUXE COATINGS

PREMIUM ROOF PAINT - HIGH GLOSS

SAFETY DATA SHEET

GHS Compliant | Date: July 2026

SECTION 1: IDENTIFICATION

Product Identifier	Deluxe Coatings Premium Roof Paint - High Gloss
Other Names	Deluxe High Gloss Premium Roof Paint / Deluxe Roof Membrane
Product Code/Type	Premium Pure Acrylic Emulsion Roof Paint
Recommended Use	Durable, weather-resistant exterior coating for granular tiles, cement tiles, fiber cement sheets, Galvanized iron, Zinalume®, prepared cladding, garage doors, gutters, downpipes, and unglazed terracotta tiles.
Restrictions	Use only as directed on technical documentation.

MANUFACTURER / SUPPLIER DETAILS

Supplier	DELUXE COATINGS
Address	Unit 5/65 Holder Way, Malaga, WA 6090
Phone / Mobile	9259 4113 / 0400 736 466
Email / Web	deluxecoatingsmalaga@gmail.com deluxecoatings.au
Emergency Phone	Contact local poison information services or seek immediate medical attention.

SECTION 2: HAZARD(S) IDENTIFICATION

GHS Classification	• Acute Toxicity, Oral: Category 4 (Harmful if swallowed) • Skin Irritation / Sensitization: Category 3 / Mild • Eye Irritation: Category 2B (Causes eye irritation)
--------------------	---

SIGNAL WORD: WARNING

Hazard Statements:

- Harmful if swallowed.
- May cause mild skin irritation.
- Causes eye irritation.

Precautionary Statements:

General: Keep out of reach of children. Read label before use.

Prevention: Ensure good ventilation during application & drying. Wear approved eye protection (AS1337). Wash thoroughly after handling.

Response:

- **IF SWALLOWED:** Do NOT induce vomiting. Call POISON CENTER or doctor.
 - **IF ON SKIN:** Wash with plenty of soap and water.
 - **IF IN EYES:** Rinse cautiously with water for several minutes; seek medical advice.
- Disposal:** Dispose of contents/container in accordance with local regulations.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL IDENTITY / COMPONENT	CAS NUMBER	PROPORTION (W/W)
100% Premium Acrylic Emulsion Binder	Proprietary	35 – 55%
Lightfast Pigments & UV Stabilizers	Commercial blend	15 – 35%
Active Anti-Fungal / Anti-Microbial Additives	Proprietary	< 2%
Ammonia (pH Adjuster)	1336-21-6	< 0.5%
Water & Non-Hazardous Additives	7732-18-5	Balance to 100%

SECTION 5: FIRE-FIGHTING MEASURES

- **Flammability:** Non-flammable water-based liquid.
- **Extinguishing Media:** Water spray, foam, dry chemical, or CO2 appropriate for surrounding fire.
- **Specific Hazards:** Thermal decomposition may release carbon oxides and trace organic vapors.
- **Protective Equipment:** Wear self-contained breathing apparatus (SCBA) and full protective bunker gear.

SECTION 4: FIRST-AID MEASURES

- **Inhalation:** Move affected person to fresh air. Ensure adequate ventilation. Seek medical attention if symptoms persist.
- **Skin Contact:** Wash area immediately with plenty of soap and water or a recognized skin cleaner.
- **Eye Contact:** Immediately rinse eyes cautiously with clean running water. Remove contact lenses if present. Continue rinsing and seek medical advice.
- **Ingestion:** Harmful if swallowed. Do NOT induce vomiting. Seek immediate medical attention.
- **Immediate Medical Attention:** Treat symptomatically based on exposure route.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- **Personal Precautions:** Ensure adequate ventilation. Avoid contact with eyes and prolonged skin contact. Wear AS1337 eye protection.
- **Environmental Precautions:** Prevent product from entering drains, waterways, or soil.
- **Containment & Cleanup:** Contain spillage with non-combustible absorbent materials (sand, earth, vermiculite). Wipe/scoop up. Brush remaining onto newspaper, allow to dry completely, and dispose via solid waste. Clean spill area immediately with warm, soapy water.

SECTION 8: EXPOSURE CONTROLS / PPE

VOC Control Parameters: VOC content < 50 g/L (EPA Method 24 / EU limits compliant).

Engineering Controls: Maintain adequate general dilution or local exhaust ventilation during mixing, application, and drying to ensure low odor & low VOC.

Personal Protective Equipment (PPE):

- **Eye/Face:** Protective goggles/glasses approved to AS1337.
- **Skin Protection:** Nitrile/rubber gloves & standard protective clothing.
- **Respiratory:** If spraying in confined spaces without adequate ventilation, wear an organic vapor/particulate respirator (AS/NZS 1716).

SECTION 7: HANDLING AND STORAGE

- **Safe Handling:** Keep out of reach of children. Ensure good ventilation during application/drying. Avoid eye & skin contact. Wear AS1337 eye protection. Do not eat, drink, or smoke when using.
- **Safe Storage:** Store in original unopened containers in a dry, well-ventilated area. Protect from freezing & direct sunlight.
- **Temperature:** Keep ambient storage between 5°C and 35°C.
- **Incompatibilities:** Strong oxidizing agents, strong acids.
- **Shelf Life:** 24 months from manufacturing date in unopened containers.

SECTION 9: PHYSICAL & CHEMICAL PROPERTIES

Appearance	Liquid - White & various vibrant colors
Finish / Odor	High Gloss Low Odor
Binder Type	100% Premium Acrylic copolymer
Solids Content	Volume: 44% ± 2% Weight: 52% ± 2%
Specific Gravity	1.23 g/cm ³ (White/Pastel) 1.14 g/cm ³ (Dark)
Viscosity / pH	95 KU at 25°C pH 8.0 – 9.0
Flash Point / VOC	Non-flammable < 20 g/L
Spreading Rate	6 – 8 m ² /L per coat at 60 µm DFT
Drying Times	Touch: 30–60 min Recoat: 2–4 hrs Full: 7–14 days

SECTION 10: STABILITY AND REACTIVITY

- **Reactivity:** Stable under normal conditions of use and storage.
- **Chemical Stability:** Stable under recommended temperatures (5°C to 35°C).
- **Hazardous Reactions:** No dangerous reactions known under normal handling.
- **Conditions to Avoid:** Extreme heat (>40°C), direct sunlight, freezing (< 5°C).
- **Incompatible Materials:** Strong oxidizing agents, strong acids, unapproved chemical additives.
- **Decomposition:** Thermal breakdown produces CO, CO2, and minor organic vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

- **Acute Toxicity:** Low acute oral and dermal toxicity.
- **Skin Contact:** Prolonged contact may cause mild irritation or skin dry-out.
- **Sensitization:** Contains active anti-fungal/anti-microbial additives; may trigger sensitivity in hyper-susceptible individuals.
- **Eye Contact:** Direct splash may cause eye irritation & temporary discomfort.
- **Ingestion:** May cause gastrointestinal discomfort, nausea, and vomiting.
- **Carcinogenicity:** Components not classified as carcinogenic or mutagenic.

SECTION 12: ECOLOGICAL INFORMATION

- **Eco-Toxicity:** Avoid contaminating drains and waterways.
- **Rainwater System Precautions:** Disconnect downpipes feeding rainwater collection tanks/storm drains prior to cleaning and coating. Leave disconnected for at least 14 days or until after two heavy rainfalls to flush residual surface surfactants.
- **Persistence & Degradability:** Acrylic binder matrix persists; organic additives biodegrade over time. Bioaccumulative potential is low.

SECTION 13: DISPOSAL CONSIDERATIONS

- **Product Disposal:** Do NOT pour leftover paint down drains or sewers. Brush unwanted liquid paint onto newspaper, allow to dry completely, and dispose via domestic solid waste.
- **Container Disposal:** Leave empty containers open in a well-ventilated area to dry completely. When dry, recycle containers via appropriate municipal recycling programs.

SECTION 14: TRANSPORT INFORMATION

UN Number	None (Non-regulated)
Shipping Name	Paint (Water-borne, non-flammable)
Hazard Class	Not classified as Dangerous Goods
Packing Group	Not applicable
Precautions	Transport in cool, upright containers. Protect from freezing and direct solar heating.

SECTION 15: REGULATORY INFORMATION

- **Eye Protection:** AS1337 compliant.
- **VOC Regulations:** Complies with EPA Method 24 / EU limits (< 50 g/L).
- **Testing Standards:** ASTM D2697 (Solids), ISO 2811 (Density), ASTM D562 (Viscosity), ASTM D1640 (Drying).
- **Poisons Schedule (SUSMP):** Not scheduled / Non-hazardous waterborne system.

SECTION 16 & 17: OTHER INFORMATION, WARRANTY & DISCLAIMER

Document Details: SDS Version 1.0 | Issue Date: July 2026 | Packaging Sizes Covered: 10L & 15L

Product Warranty & Coverage:

Deluxe Coatings warrants that this product, when applied in strict accordance with instructions on packaging and the TDS, will meet published performance specifications. Warranty extends up to 10 years for exterior applications and 12 years for interior applications. Coverage includes product replacement or purchase price refund only. Excludes failure resulting from inadequate surface preparation, structural movement, hydrostatic pressure, rising damp, improper thinning, or mechanical damage. Deluxe Coatings is not liable for labor, scaffolding, or consequential damages.

Disclaimer & Manufacturer's Note:

Information provided in good faith based on laboratory testing and field experience. Users must determine product suitability for intended use. Always perform a test patch in an inconspicuous area if unsure of substrate condition. Deluxe Coatings reserves the right to update product formulations without prior notice.