

SECTION 1: IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Identifier: Deluxe Coatings Premium Wall Paint - Low Sheen

Other Identification: Deluxe Interior / Exterior Wall Paint — Low Sheen

Product Code/Type: 100% Premium Acrylic Latex waterborne architectural coating

Recommended Use: Decorative & protective coating for interior/exterior architectural substrates (masonry, drywall, timber, concrete, brickwork).

Restrictions on Use: Use only as directed on technical documentation.

MANUFACTURER / SUPPLIER DETAILS

Company: DELUXE COATINGS

Address: Unit 5/65 Holder Way, Malaga, WA 6090

Phone: 9259 4113 | Mobile: 0400 736 466

Email: deluxecoatingsmalaga@gmail.com

Website: deluxecoatings.au

Emergency: **Contact local poison information services or seek immediate medical attention.**

SECTION 2: HAZARD(S) IDENTIFICATION

GHS Classification

- Acute Toxicity, Oral:** Category 4 (Harmful if swallowed)
- Skin Irritation / Sensitization:** Category 3 / Mild (Contains minor active anti-fungal/anti-microbial additives & trace volatile bases/ammonia)
- Eye Irritation:** Category 2B (May cause eye irritation on contact)

Precautionary Statements

General: Keep out of reach of children. Read label before use.

Prevention: Ensure good ventilation during application and drying. Wear approved eye protection (AS1337). Wash thoroughly after handling.

SIGNAL WORD: WARNING

HAZARD STATEMENTS

- Harmful if swallowed.
- May cause mild skin irritation.
- Causes eye irritation.

Response:

- IF SWALLOWED:** Do NOT induce vomiting. Call a POISON CENTER or doctor/physician.
- IF ON SKIN:** Wash with plenty of soap and water.
- IF IN EYES:** Rinse cautiously with water for several minutes; seek medical advice.

Disposal: Dispose of contents/container in accordance with local environmental regulations.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL IDENTITY / COMPONENT	CAS NUMBER	PROPORTION (W/W)
100% Premium Acrylic Emulsion Binder	Proprietary	30 – 50%
Lightfast Pigments & UV Stabilizers	Commercial blend	10 – 30%
Active Anti-Fungal / Anti-Microbial Additives	Proprietary	< 2%

CHEMICAL IDENTITY / COMPONENT	CAS NUMBER	PROPORTION (W/W)
Ammonia (pH Adjuster)	1336-21-6	< 0.5%
Water & Non-Hazardous Additives	7732-18-5	Balance to 100%

SECTION 4: FIRST-AID MEASURES

- Inhalation:** Move affected person to fresh air. Ensure adequate ventilation. Seek medical attention if symptoms persist.
- Skin Contact:** Wash area immediately with plenty of soap and water or a recognized skin cleaner.
- Eye Contact:** Immediately rinse cautiously with clean running water. Remove contact lenses if present. Seek medical advice.
- Ingestion:** **Harmful if swallowed.** Do NOT induce vomiting. Seek immediate medical attention.

Immediate Medical Attention: Treat symptomatically based on exposure route.

SECTION 5: FIRE-FIGHTING MEASURES

- Flammability:** Non-flammable water-based liquid.
- Suitable Extinguishing Media:** Water spray, foam, dry chemical, or CO2 appropriate for surrounding fire.
- Specific Hazards:** Thermal decomposition may release carbon oxides and trace organic vapors.
- Firefighter Protection:** Wear self-contained breathing apparatus (SCBA) and full protective bunker gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- Personal Precautions:** Ensure adequate ventilation. Avoid contact with eyes and prolonged contact with skin. Wear PPE (AS1337 eye protection).
- Environmental Precautions:** Prevent product from entering drains, waterways, or soil.
- Containment & Cleanup:** Contain spillage with absorbent materials (sand, earth, vermiculite). Wipe or scoop up. Brush remaining onto newspaper to dry before solid waste disposal. Clean area with warm, soapy water.

SECTION 7: HANDLING AND STORAGE

- Safe Handling:** Keep out of reach of children. Ensure good ventilation. Avoid skin/eye contact. Wear AS1337 eye protection. Do not eat, drink, or smoke during use.
- Storage Conditions:** Store in original, unopened containers in a dry, well-ventilated area. Protect from freezing and direct sunlight.
- Storage Temp:** 5°C to 35°C | **Shelf Life:** 24 months
- Incompatibilities:** Strong oxidizing agents, strong acids.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

- Control Parameters (VOC):** VOC content < 50 g/L (EPA Method 24 / EU limits compliant).
- Engineering Controls:** Maintain adequate general dilution or local exhaust ventilation during mixing, application, and drying to ensure low odor and low VOC levels.

Personal Protective Equipment (PPE)

- **Eye/Face:** Protective goggles/glasses approved to AS1337 must be worn.
- **Skin:** Nitrile or rubber protective gloves and standard protective clothing.
- **Respiratory:** If spraying in confined spaces without adequate ventilation, wear an approved organic vapor/particulate respirator (AS/NZS 1716).

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PROPERTY	VALUE / DESCRIPTION	PROPERTY	VALUE / DESCRIPTION
Appearance	Liquid - White & tintable bases	pH Value	8.0 – 9.0 (Adjusted using Ammonia)
Finish	Low-Sheen / Eggshell (10-15% @60°)	Flash Point	Non-flammable
Odor	Low Odor	VOC Content	< 50 g/L
Binder Type	100% Premium Acrylic copolymer	Spreading Rate	10 – 12 m²/L per coat at 60 µm DFT
Solids Content	Volume: 40% ± 2% Weight: 52% ± 2%	Freezing Point	Protect from freezing (< 5°C)
Specific Gravity	Approx. 1.15 – 1.35 g/cm³	Solubility in Water	Dispersible prior to curing; cured film is water repellent
Viscosity at 23°C	95–100 KU (Krebs Units) at 25°C	Drying Times	Touch: 30–60m Recoat: 2–4h Full: 7–14d

SECTION 10: STABILITY AND REACTIVITY

Reactivity & Stability: Stable under normal conditions (5°C to 35°C).

Hazardous Reactions: None known under normal handling.

Conditions to Avoid: Extreme heat (>40°C), direct sunlight, freezing (<5°C).

Incompatible Materials: Strong oxidizing agents, strong acids, unapproved additives.

Decomposition Products: Carbon monoxide, carbon dioxide, minor organic vapors under fire.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity: Low acute oral and dermal toxicity.

Skin Contact: Prolonged contact may cause mild irritation or dry-out.

Sensitization: Active additives may trigger sensitivity in hyper-susceptible individuals.

Eye Contact: Direct splash may cause irritation and temporary discomfort.

Ingestion: May cause gastrointestinal discomfort, nausea, vomiting.

Carcinogenicity / Mutagenicity: Not classified under GHS limits.

SECTION 12: ECOLOGICAL INFORMATION

Eco-Toxicity: Avoid contaminating drains and waterways.

Rainwater System Precautions: Disconnect all downpipes feeding rainwater tanks or storm drains prior to cleaning/coating. Leave disconnected for at least 14 days or until after first two heavy rainfalls to flush surface surfactants.

Persistence & Degradability: Acrylic matrix persists; organic additives biodegrade over time. Bioaccumulative potential is low.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Treatment / Product Disposal: Do NOT pour leftover paint down drains or sewers. Brush out unwanted liquid paint on newspaper, allow to dry completely, and dispose of via domestic solid waste collections.

Container Disposal: Leave empty containers open in a well-ventilated area to dry completely. Recycle via municipal programs when dry.

SECTION 14: TRANSPORT INFORMATION

UN Number: None (Non-regulated)

UN Proper Shipping Name: Paint (Water-borne, non-flammable)

SECTION 15: REGULATORY INFORMATION

Standards Compliance:

- **Eye Protection:** AS1337 compliant
- **VOC Regulations:** EPA Method 24 / EU limits (< 50 g/L)

Transport Hazard Class: Not classified as Dangerous Goods

Packing Group: Not applicable | **Hazards:** Non-hazardous

Precautions: Transport upright in cool conditions. Protect from freezing and direct sunlight.

• **Testing Standards:** ASTM D2697, ISO 2811, ASTM D562, ASTM D1640

Poisons Schedule (SUSMP): Not scheduled / Non-hazardous waterborne system.

SECTION 16 & 17: ADDITIONAL INFO, WARRANTY & LEGAL DISCLAIMER

SDS Version: 1.0 | **Issue Date:** July 2026

Packaging Sizes Covered: 1L, 2L, 4L, 10L & 15L

Product Warranty

Deluxe Coatings warrants that this product, when applied in strict accordance with instructions on the packaging and Technical Data Sheet (TDS), will meet published performance specifications. Warranty extends for up to **10 years (exterior)** and **12 years (interior)** from purchase date.

Limitations & Legal Disclaimer

Limitations: Covers product replacement or refund of purchase price only. Excludes failure due to inadequate surface preparation, structural movement, hydrostatic pressure, rising damp, improper thinning, or mechanical damage. Not liable for labor or consequential damages.

Manufacturer Note: Perform a test patch in an inconspicuous area if unsure of substrate condition. Deluxe Coatings reserves the right to update formulations without notice. Reference the most current TDS at deluxecoatings.au.