

DELUXE COATINGS

Premium Quality Paints, Built to Last

SAFETY DATA SHEET (SDS)

Product: Premium Wall Paint - Matt

Date: July 2026 | Version: 1.0

Website: deluxecoatings.au

Emergency Phone: Poison Info / 000

1. IDENTIFICATION OF MATERIAL & SUPPLIER

Product Identifier: Deluxe Coatings Premium Wall Paint — Matt

Other Identification: Deluxe Interior / Exterior Wall Paint — Matt

Product Code/Type: 100% Premium Acrylic Latex waterborne architectural coating

Recommended Use: Decorative & protective waterborne paint for interior and exterior architectural substrates (masonry, concrete, cement plaster, drywall, brickwork, fiber cement, sound timber).

Restrictions on Use: Use only as directed on technical documentation.

Supplier Details

Company: DELUXE COATINGS

Address: Unit 5/65 Holder Way, Malaga, WA 6090

Phone: 9259 4113 | **Mobile:** 0400 736 466

Email: deluxecoatingsmalaga@gmail.com

2. HAZARD(S) IDENTIFICATION

GHS CLASSIFICATION

WARNING

- **Acute Toxicity, Oral (Cat 4):** Harmful if swallowed.
- **Skin Irritation / Sensitization (Cat 3/Mild):** Minor active anti-fungal/anti-microbial additives & trace ammonia.
- **Eye Irritation (Cat 2B):** May cause eye irritation on contact.

Precautionary Statements

General: Keep out of reach of children. Read label before use.

Prevention: Ensure good ventilation. Wear approved eye protection (AS1337). Wash thoroughly after handling.

Response:

- **IF SWALLOWED:** Do NOT induce vomiting. Call POISON CENTER or doctor.
- **IF ON SKIN:** Wash with plenty of soap and water.
- **IF IN EYES:** Rinse cautiously with water for several minutes.

Disposal: Dispose of contents/container in accordance with local regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Identity / Component	CAS Number	Proportion (w/w)
100% Premium Acrylic Emulsion Binder	Proprietary	35 – 55%
Lightfast Pigments & UV Stabilizers	Commercial blend	15 – 35%
Active Anti-Fungal / Anti-Microbial Additives	Proprietary	< 2%
Ammonia (pH Adjuster)	1336-21-6	< 0.5%
Water & Non-Hazardous Additives	7732-18-5	Balance to 100%

4. FIRST-AID MEASURES

Inhalation: Move to fresh air. Ensure adequate ventilation. Seek medical attention if symptoms persist.

Skin Contact: Wash area immediately with plenty of soap and water or recognized skin cleaner.

Eye Contact: Immediately rinse cautiously with clean running water. Remove contact lenses if present and easy to do. Continue rinsing; seek medical advice.

5. FIRE-FIGHTING MEASURES

Flammability: Non-flammable water-based liquid.

Extinguishing Media: Water spray, foam, dry chemical, or CO2 appropriate for surrounding fire.

Specific Hazards: Thermal decomposition may release carbon oxides and trace organic vapors.

Ingestion: Harmful if swallowed. Do NOT induce vomiting. Seek immediate medical attention.

Immediate Attention: Treat symptomatically based on exposure route.

Firefighter Protection: Wear self-contained breathing apparatus (SCBA) and full protective bunker gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Ensure adequate ventilation. Avoid contact with eyes and prolonged skin contact. Wear AS1337 eye protection.

Environmental Precautions: Prevent product from entering drains, waterways, or soil.

Containment & Cleanup: Contain with absorbent materials (sand, earth, vermiculite). Scoop/wipe up. Brush residue onto newspaper, dry completely, and dispose via solid waste. Clean area with warm soapy water.

7. HANDLING AND STORAGE

Safe Handling: Keep out of reach of children. Ensure good ventilation. Avoid contact with eyes/skin. Wear AS1337 eye protection. Do not eat, drink, or smoke during use.

Storage Conditions: Store in original unopened containers in dry, well-ventilated area. Protect from freezing & direct sunlight (5°C to 35°C).

Incompatibilities: Strong oxidizing agents, strong acids.

Shelf Life: 24 months from mfg date in unopened containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters (VOC): < 50 g/L (EPA Method 24 / EU limits compliant).

Engineering Controls: Maintain adequate dilution/exhaust ventilation during mixing, application, and drying.

Personal Protective Equipment (PPE)

Eye/Face: AS1337 approved protective goggles/glasses.

Skin: Nitrile or rubber protective gloves and standard protective clothing.

Respiratory: In confined spaces without adequate ventilation, wear AS/NZS 1716 organic vapor/particulate respirator.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid - White & tintable bases
Finish	Matt/Flat (>5% @ 60°)
Odor / Binder	Low Odor / 100% Acrylic copolymer
Solids Content	Vol: 45% ± 2% Wt: 55% ± 2%
Specific Gravity	Approx. 1.2 – 1.4 g/cm³
Viscosity (23°C)	100 - 120 KU (Krebs Units)
pH Value	8.0 – 9.0 (Ammonia adjusted)
Flash Point / VOC	Non-flammable / < 50 g/L
Spreading Rate	10 – 12 m²/L per coat @ 60 µm DFT
Drying Times	Touch: 30-60m Recoat: 2-4h Cure: 7-14d

10. STABILITY AND REACTIVITY

Reactivity: Stable under normal conditions of use and storage.

Chemical Stability: Stable under recommended temperatures (5°C to 35°C).

Hazardous Reactions: None known under normal handling.

Conditions to Avoid: Extreme heat (>40°C), direct sunlight, freezing (<5°C).

Incompatible Materials: Strong oxidizing agents, strong acids, unapproved additives.

Decomposition Products: CO, CO2, and minor organic vapors under fire conditions.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity: Low acute oral and dermal toxicity.

Skin Contact: Prolonged contact may cause mild irritation or dry-out.

Sensitization: Contains anti-fungal/microbial additives; may trigger sensitivity in hyper-susceptible individuals.

Eye Contact: Direct splash may cause eye irritation and discomfort.

Ingestion: May cause gastrointestinal discomfort, nausea, vomiting.

Carcinogenicity: Not classified as carcinogenic or mutagenic under GHS.

12. ECOLOGICAL INFORMATION

Eco-Toxicity: Avoid contaminating drains and waterways.

Rainwater Systems: Disconnect downpipes prior to cleaning/coating. Leave disconnected for 14 days or until after 2 heavy rainfalls to flush residual surfactants.

Persistence / Bioaccumulation: Acrylic matrix persists; additives biodegrade. Bioaccumulation potential is low.

13. DISPOSAL CONSIDERATIONS

Product Disposal: Do NOT pour leftover paint down drains/sewers. Brush unwanted liquid paint onto newspaper, allow to dry completely, and dispose of via domestic solid waste.

Container Disposal: Leave open in well-ventilated area to dry. Recycle dry containers via municipal recycling.

14. TRANSPORT INFORMATION

UN Number / Class: None (Non-regulated / Not Dangerous Goods)

Proper Shipping Name: Paint (Water-borne, non-flammable)

Packing Group / Env Hazards: Not applicable / Non-hazardous

Special Precautions: Transport upright in cool conditions. Prevent freezing and direct solar heating.

15 & 16. REGULATORY & OTHER INFO

Standards Compliance: AS1337 (Eye Protection), EPA Method 24 / EU limits (<50 g/L VOC). ASTM D2697, ISO 2811, ASTM D562, ASTM D1640.

Poisons Schedule: Not scheduled (SUSMP).

SDS Version & Date: Version 1.0 (Issued July 2026)

Packaging Sizes: 1L, 2L, 4L, 10L & 15L

17. LEGAL DISCLAIMER & PRODUCT WARRANTY

Product Warranty: Deluxe Coatings warrants that this product, when applied in strict accordance with the instructions on packaging and Technical Data Sheet (TDS), meets published specifications. Covers up to **10 years exterior** and **12 years interior** from purchase date.

Limitations: Product replacement or refund of purchase price only. Excludes failure from inadequate surface preparation, structural movement, hydrostatic pressure, rising damp, improper thinning, or mechanical damage. Not liable for labor, scaffolding, or consequential damages.

Disclaimer & Note: Recommendations are provided in good faith. Users must determine suitability for intended use. Perform a test patch in an inconspicuous area prior to full application. Deluxe Coatings reserves the right to update formulations without prior notice.