

SECTION 1: IDENTIFICATION OF MATERIAL & SUPPLIER

Product Identifier	Deluxe Coatings SUPER-COVER Ceiling Paint
Other Names	Deluxe Interior / Exterior Wall Paint - Super Cover Ceiling Paint
Product Code/Type	100% Premium Acrylic Latex waterborne architectural Ceiling coating
Recommended Use	Premium water-based smooth interior emulsion for interior ceilings, wall surfaces, high-critical-lighting areas, cornices, ceiling roses, picture rails, and upper interior wall areas.
Restrictions	Use only as directed on technical documentation.

MANUFACTURER & SUPPLIER DETAILS

DELUXE COATINGS

Address:	Unit 5/65 Holder Way, Malaga, WA 6090
Phone:	9259 4113
Mobile:	0400 736 466
Email:	deluxecoatingsmalaga@gmail.com
Website:	deluxecoatings.au

EMERGENCY PHONE NUMBER: Contact local poisons information services or seek immediate medical attention.

SECTION 2: HAZARD(S) IDENTIFICATION

GHS Classification:

- **Acute Toxicity, Oral (Category 4)** – Harmful if swallowed.
- **Skin Irritation / Sensitization (Category 3 / Mild)** – Contains minor active anti-fungal/anti-microbial additives and trace volatile bases (ammonia).
- **Eye Irritation (Category 2B)** – May cause eye irritation on contact.

SIGNAL WORD: WARNING

Hazard Statements:

- Harmful if swallowed.
- May cause mild skin irritation.
- Causes eye irritation.

Precautionary Statements:

General	Keep out of reach of children. Read label before use.
Prevention	Ensure good ventilation during application and drying. Wear approved eye protection (AS1337). Wash thoroughly after handling.
Response	IF SWALLOWED: Do NOT induce vomiting. Call a POISON CENTER or doctor/physician. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes; seek medical advice.
Disposal	Dispose of contents/container in accordance with local environmental regulations.

SECTION 3: COMPOSITION / INGREDIENTS

Component	CAS Number	Proportion
100% Premium Acrylic Emulsion Binder	Proprietary	35 – 55%
Lightfast Pigments & UV Stabilizers	Commercial blend	20 – 40%
Active Anti-Fungal / Anti-Microbial Additives	Proprietary	< 2%
Ammonia (pH Adjuster)	1336-21-6	< 0.5%
Water & Non-Hazardous Additives	7732-18-5	Balance to 100%

SECTION 5: FIRE-FIGHTING MEASURES

Flammability: Non-flammable water-based liquid.

Suitable Extinguishing Media: Water spray, foam, dry chemical, or carbon dioxide (CO₂) appropriate for surrounding fire.

Specific Hazards: Thermal decomposition may release carbon oxides and trace organic vapors.

Protective Equipment: Wear self-contained breathing apparatus (SCBA) and full protective bunker gear.

SECTION 7: HANDLING & STORAGE

Safe Handling: Keep out of reach of children. Ensure good ventilation. Avoid contact with eyes and skin. Wear AS1337 approved eye protection. Do not eat, drink, or smoke when using.

Storage Conditions: Store in original, unopened containers in a dry, well-ventilated area. Protect from freezing and direct sunlight.

Storage Temperature: 5°C to 35°C.

Incompatibilities: Strong oxidizing agents, strong acids.

Shelf Life: 24 months from manufacturing date in unopened containers.

SECTION 4: FIRST-AID MEASURES

- **Inhalation:** Move affected person to fresh air. Ensure adequate ventilation. If symptoms persist, seek medical attention.
- **Skin Contact:** Wash area immediately with plenty of soap and water or a recognized skin cleaner.
- **Eye Contact:** Immediately rinse eyes cautiously with clean running water. Remove contact lenses if present and easy to do. Continue rinsing and seek medical advice.
- **Ingestion:** Harmful if swallowed. Do NOT induce vomiting. Seek immediate medical attention.
- **Immediate Medical Attention:** Treat symptomatically based on exposure route.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Ensure adequate ventilation. Avoid eye contact and prolonged skin contact. Wear AS1337 approved eye protection.

Environmental Precautions: Prevent product from entering drains, waterways, or soil.

Containment & Cleanup: Contain spillage with non-combustible absorbent materials (sand, earth, vermiculite). Wipe or scoop up. Brush remaining material onto newspaper, allow to dry, and dispose via solid waste. Clean area with warm, soapy water.

SECTION 8: EXPOSURE CONTROLS / PPE

Control Parameters (VOC): VOC content < 50 g/L (EPA Method 24 / EU limits compliant).

Engineering Controls: Maintain adequate general dilution or local exhaust ventilation during mixing, application, and drying to ensure low odor/VOC levels.

Personal Protective Equipment (PPE):

- **Eye/Face:** Protective goggles/glasses approved to AS1337 must be worn.
- **Skin:** Protective gloves (nitrile or rubber) and standard protective clothing.
- **Respiratory:** If spraying in confined spaces without adequate ventilation, wear an approved organic vapor/particulate respirator meeting AS/NZS 1716.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid - White & tintable Pastel bases	Finish	Ultra-Flat/Matt (<2% @ 60°)
Odor	Low Odor	Binder Type	100% Premium Acrylic copolymer
Solids Content	Volume: 55% ± 2% Weight: 65% ± 2%	Specific Gravity (SG)	Approx. 1.3 – 1.6 g/cm³
Viscosity at 23°C	100-120 KU (Krebs Units) at 25°C	pH Value	8.0 – 9.0 (Adjusted using Ammonia)
Flash Point	Non-flammable	VOC Content	< 50 g/L (Low VOC)
Theoretical Spreading Rate	10 – 12 m²/L per coat at 60 µm DFT	Melting / Freezing Point	Not determined (protect from freezing < 5°C)
Solubility in Water	Dispersible prior to curing; cured film is water repellent	Drying Times (25°C, 50% RH)	Touch Dry: 30–60 min Recoat: Min 2–4 hrs Full Cure: 7–14 days

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Stable under normal conditions of use and storage.

Chemical Stability: Stable under recommended storage temperatures (5°C to 35°C).

Hazardous Reactions: No dangerous reactions known under normal handling.

Conditions to Avoid: Extreme heat (>40°C), direct sunlight, freezing (< 5°C).

Incompatible Materials: Strong oxidizing agents, strong acids, or unapproved chemical additives.

Hazardous Decomposition: Thermal decomposition under fire may produce CO, CO2, and minor organic vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity: Low acute oral and dermal toxicity.

Skin Contact: Prolonged/repeated contact may cause mild irritation or skin dry-out.

Sensitization: Active anti-fungal/anti-microbial additives may trigger sensitivity in hyper-susceptible individuals.

Eye Contact: Direct splash may cause eye irritation and temporary discomfort.

Ingestion: May cause gastrointestinal discomfort, nausea, and vomiting.

Carcinogenicity / Mutagenicity: Not classified as carcinogenic or mutagenic under GHS limits.

SECTION 12: ECOLOGICAL INFORMATION

Eco-Toxicity: Avoid contaminating drains and waterways.

Rainwater System Precautions: Disconnect all downpipes feeding rainwater collection tanks or storm drains prior to cleaning and coating. Leave downpipes disconnected for at least 14 days or until after the first two heavy rainfalls to flush residual surface surfactants.

Persistence & Degradability: Acrylic binder matrix persists; organic additives biodegrade over time.

Bioaccumulative Potential: Low potential.

SECTION 13: DISPOSAL CONSIDERATIONS

Product Disposal: Do NOT pour leftover paint down drains or sewers. Unwanted liquid paint should be brushed out on newspaper, allowed to dry completely, and disposed of via domestic solid waste collections.

Container Disposal: Empty paint containers should be left open in a well-ventilated area to dry out completely. When dry, recycle containers via appropriate municipal recycling programs.

SECTION 14: TRANSPORT INFORMATION

UN Number	None (Non-regulated)
UN Proper Shipping Name	Paint (Water-borne, non-flammable)
Transport Hazard Class	Not classified as Dangerous Goods
Packing Group	Not applicable
Environmental Hazards	Non-hazardous for transport
Special Precautions	Transport in cool, upright containers. Prevent freezing and direct solar heating.

SECTION 15: REGULATORY INFORMATION

Standards Compliance:

- **Eye Protection:** AS1337 compliant.
- **VOC Regulations:** EPA Method 24 / EU limits compliant (< 50 g/L).
- **Testing Standards:** ASTM D2697 (Solids), ISO 2811 (Density), ASTM D562 (Viscosity), ASTM D1640 (Drying).
- **Poisons Schedule (SUSMP):** Not scheduled / Non-hazardous waterborne system.

SECTION 16: OTHER INFORMATION & PACKAGING

SDS Version: 1.0 | Issue Date: July 2026 | Packaging Sizes Covered: 1L, 2L, 4L, 10L & 15L

SECTION 17: LEGAL DISCLAIMER & PRODUCT WARRANTY

Product Warranty: Deluxe Coatings warrants that this product, when applied in strict accordance with the instructions on the packaging and this Technical Data Sheet (TDS), will meet its published performance specifications. This warranty extends for up to 10 years for exterior applications and 12 years for interior applications from the date of purchase.

Limitations & Coverage: This warranty covers product replacement or refund of the purchase price only. It excludes failure resulting from inadequate surface preparation, structural movement, hydrostatic pressure, rising damp, improper thinning, or mechanical damage. To the maximum extent permitted by law, Deluxe Coatings is not liable for labor, scaffolding, or consequential damages.

Disclaimer & Notice: Information and recommendations in this document are provided in good faith based on laboratory testing and field experience. Because substrate conditions, application methods, and environmental factors are beyond our control, users must determine the suitability of the product for their intended use. For complete technical specifications and application guidance, refer to the corresponding Technical Data Sheet (TDS).

MANUFACTURER'S NOTE: Always perform a test patch in an inconspicuous area if you are unsure of the substrate's condition. For any additional technical support, please contact the Malaga office. Deluxe Coatings reserves the right to update product formulations and technical data without prior notice. Always ensure you are referencing the most current TDS available on the official Deluxe Coatings portal.